




ライン No.	ランプ No.	形式	定 格		明るさ (Lumens Approx.)	平均寿命 (時間)	外形寸法 (mm)		フィラメント 形	口 金	Fig.
			電圧 (V)	電流 (A)			径 D ±1	径 L ±2			
26-1	H-5552	TE	6	0.06	1.2	5,000	10	28	C-2R	E10/14	1
- 2	*H-5555	TE	6	0.50	25.0	1,000	10	28	C-2R	E10/14	1
- 3	H-5553	TE	6.3	0.15	5.0	5,000	10	28	C-2R	E10/14	1
- 4	H-5556	TE	8	0.08	2.5	5,000	10	28	C-2R	E10/14	1
- 5	H-5558	TE	8	0.15	6.0	5,000	10	28	C-2R	E10/14	1
- 6	H-5561	TE	12	0.06	2.0	5,000	10	28	C-2V	E10/14	2
- 7	H-5562	TE	12	0.06	2.0	10,000	10	28	C-2F	E10/14	3
- 8	H-5565	TE	18	0.11	10.0	1,000	10	28	C-2V	E10/14	2
- 9	H-5568	TE	28	0.04	4.3	1,000	10	28	C-2F	E10/14	3
-10	*H-1235	TB	6	0.50	25.0	1,000	10	28	C-2R	BA9S/13	4
-11	H-1201	TB	6.3	0.10	3.0	3,000	10	28	C-2R	BA9S/13	4
-12	H-1236	TB	6.3	0.35	10.0	5,000	10	28	CC-6	BA9S/13	7
-13	H-1203	TB	6.3	0.15	5.0	5,000	10	28	C-2R	BA9S/13	4
-14	H-1211	TB	12	0.06	2.0	10,000	10	28	C-2F	BA9S/13	6
-15	H-1216	TB	14	0.10	7.0	3,000	10	28	C-2V	BA9S/13	5
-16	*H-1218	TB	24	0.25	15.3	5,000	10	28	CC-6	BA9S/13	8
-17	*H-1221	TB	28	0.04	4.3	1,000	10	28	C-2F	BA9S/13	6
-18	*H-1223	TB	28	0.17	44.0	500	10	28	C-2F	BA9S/13	6

▶ *印 MIL 認定品があります。(P-29 参照)
 ▶ *印はガス入り。
 ▶ 適合ランプソケット (P-33 参照)

TE タイプ



TB タイプ



ライン No.	ランプ No.	定 格		明るさ (Lumens Approx.)	平均寿命 (時間)	外 形 寸 法 (mm)			フィラメント 形	口 金	Fig.
		電圧 (V)	電流 (A)			径 (D) (Max.)	全長 (L) (Max.)	光中心距離 (L.C.L.)			
27-1	H-6011	4.0	1.0	18	2,000	11	30	18 ± 1	C-6	BA9S/13	9
- 2	H-6012	5.0	1.0	38	10,000	11	30	18 ± 1	C-6	BA9S/13	9
- 3	H-6013	6.0	1.0	65	1,000	11	30	18 ± 1	C-6U	BA9S/13	10
- 4	H-6015	6.0	1.0	60	1,000	19.5	36	20 ± 1	C-6	BA15S/19	11
- 5	H-0751	6.0	1.0	70	300	19.5	36	20 ± 1	C-6	BA15S/19	11
- 6	H-0753	6.0	1.5	95	1,000	19.5	36	20 ± 1	C-6	BA15S/19	11
- 7	H-6021	6.0	2.0	130	1,200	19.5	36	20 ± 1	C-6	BA15S/19	11
- 8	H-6023	6.0	2.0	140	1,000	19.5	36	20 ± 1	C-6U	BA15S/19	12
- 9	H-6024	6.0	2.0	140	1,000	19.5	36	20 ± 1	P-6Z	BA15S/19	13
-10	H-6025	6.0	2.0	140	1,000	19.5	36	20 ± 1	P-6U	BA15S/19	14
-11	H-6026	6.0	2.0	140	1,000	19.5	36	20 ± 1	P-6U	BA15D/19	15
-12	H-6035	6.0	3.0	190	1,000	19.5	36	20 ± 1	C-6	BA15S/19	11
-13	H-0755	6.0	3.0	230	400	19.5	36	20 ± 1	C-6	BA15S/19	11
-14	H-6037	6.0	3.0	200	1,000	19.5	36	20 ± 1	C-6U	BA15S/19	12
-15	H-6038	6.0	3.0	200	1,000	19.5	36	20 ± 1	P-6Z	BA15S/19	13
-16	H-0761	6.0	3.0	230	450	19.5	36	20 ± 1	P-6U	BA15S/19	14
-17	H-6039	6.0	3.0	230	450	19.5	36	20 ± 1	P-6U	BA15D/19	15
-18	H-0773	6.0	4.0	250	2,500	26	50	30 ± 1.5	P-6Z	BA15S/19	16
-19	H-0775	6.0	5.0	320	1,000	26	50	30 ± 1.5	C-6U	BA15S/19	17
-20	H-6043	6.0	5.0	500	100	26	50	30 ± 1.5	P-6Z	BA15D/19	18
-21	H-6031	12.0	3.3	450	300	31	49.5	26.5 ± 1.5	CC-6	BA15S/19	19
-22	H-6041	10.0	7.0	1,500	100	41	67	39.5 ± 1.5	P-6U	B15S/28 × 24	20
-23	H-6051	15.0	10.0	2,300	350	51	82	44 ± 1.5	P-8Z	B15S/28 × 24	21

▶ 適合ランプソケット (P-33 参照)
 ▶ Fig.9 ~ 21 すべてガス入り

