


小型パイロットランプ

ライン No.	ランプ No.	形式	定 格		明るさ (Lumens Approx.)	平均寿命 (時間)	外形寸法 (mm)		フィラメント 形 状	口 金	Fig.
			電圧 (V)	電流 (A)			径 D ±1	径 L ±2			
26- 1	H-5552	TE	6	0.06	1.2	5,000	10	28	C-2R	E10/14	1
- 2	※H-5555	TE	6	0.50	25.0	1,000	10	28	C-2R	E10/14	1
- 3	H-5553	TE	6.3	0.15	5.0	5,000	10	28	C-2R	E10/14	1
- 4	H-5556	TE	8	0.08	2.5	5,000	10	28	C-2R	E10/14	1
- 5	H-5558	TE	8	0.15	6.0	5,000	10	28	C-2R	E10/14	1
- 6	H-5561	TE	12	0.06	2.0	5,000	10	28	C-2V	E10/14	2
- 7	H-5562	TE	12	0.06	2.0	10,000	10	28	C-2F	E10/14	3
- 8	H-5565	TE	18	0.11	10.0	1,000	10	28	C-2V	E10/14	2
- 9	H-5568	TE	28	0.04	4.3	1,000	10	28	C-2F	E10/14	3
-10	※H-1235	TB	6	0.50	25.0	1,000	10	28	C-2R	BA9S/13	4
-11	H-1201	TB	6.3	0.10	3.0	3,000	10	28	C-2R	BA9S/13	4
-12	H-1236	TB	6.3	0.35	10.0	5,000	10	28	CC-6	BA9S/13	7
-13	H-1203	TB	6.3	0.15	5.0	5,000	10	28	C-2R	BA9S/13	4
-14	H-1211	TB	12	0.06	2.0	10,000	10	28	C-2F	BA9S/13	6
-15	H-1216	TB	14	0.10	7.0	3,000	10	28	C-2V	BA9S/13	5
-16	※H-1218	TB	24	0.25	15.3	5,000	10	28	CC-6	BA9S/13	8
-17	*H-1221	TB	28	0.04	4.3	1,000	10	28	C-2F	BA9S/13	6
-18	*H-1223	TB	28	0.17	44.0	500	10	28	C-2F	BA9S/13	6

- ▶ *印 MIL 認定品があります。(P-29 参照)
- ▶ ※印はガス入り。
- ▶ 適合ランプソケット (P-33 参照)

TE タイプ



TB タイプ

